

# PARAMOUNT STANDARD BARRIER

Data Sheet STB

The **Paramount** Standard Barrier is the ideal solution for vehicle flow rates of up to 300 per Hour, and is designed primarily for car park control.

- A popular choice for businesses, and local Authority Premises.
- Smooth and Powerful operation via a motor, gearbox drive unit, controlled through an inverter for precise control.

Operation of the barrier is completely non-hydraulic eliminating leaking pipes and unions and providing low service costs with higher levels of reliability.

## Specifications

1. Maximum span (boom) 6.00 metres with pole only barrier.
2. Maximum span (boom) 5.00 metres with a pole and lower skirt.
3. Operating time:- 4 Seconds.
4. Colour :- Cabinet Std – Blue, Pole - red (optional white flashes)
5. Optional Powder Coating in any RAL colour.



## Options

- a. Collapsible curtain
- b. Tip support
- c. Warning
- d. Boom lights
- e. Traffic Lights

## Control Types

- a. Push Buttons : open/close/stop.
- b. Radio receiver.
- c. Inductive loops.
- d. Card readers (Proximity/Swipe)
- e. (AVR) automatic vehicle recognition

Or any other access control product shown on the Access Control pages

Paramount Security Group, Nevada Lane, Burslem, Stoke On Trent, England  
[www.paramountsecuritygroup.com](http://www.paramountsecuritygroup.com) Telephone 01782 833333 fax 01782 832222